

ALL PURPOSE HAND CLEANER WITH LANOLIN PART NO. 53108

PHYSICAL PROPERTIES

Physical State	Thick, creamy
Odor	Banana odor
Color/Appearance	Pink
Specific Gravity	0.871
Flash Point	120°F (49°C)
FP Method	PM COC
pH	7.8
Density lbs/Gal.	7
Boiling/Cond. Point	168°F (76°C)
Melting/Freezing Point	Not established
Solubility	Complete in water
Evaporation Rate	Not established
VOC %	332.95 g/L



DESCRIPTION

Dynatex® All Purpose Hand Cleaner is a precisely formulated blend of surfactants, emulsifiers, and skin conditioners. The balanced mixture provides optimum cleaning potential for your hands without harshness or irritability.

Dynatex® All Purpose Hand Cleaner with lanolin is a creamy formula that liquefies and gently lifts grease, grime and stains from the hands safely with or without water. **Dynatex® All Purpose Hand Cleaner** leaves hands cleaned and conditioned without the greasy feeling and strong odors of competitive brands. Contains lanolin and skin care emollients to aid in healing rough, dry and overused hands.

FEATURES

- Removes grease, grime, oils, soil, gasket cement, glues and inks
- Cleans with or without water
- Won't clog drains
- Contains lanolin to keep hands smooth
- Pleasant smelling
- Leaves hands smooth, not sticky
- Cleans without use of petroleum solvents
- Pumice free

Removes:

- Grease
- Stains
- Paint
- Tars
- Printer's ink
- Fish odors and much more.....

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® All Purpose Hand Cleaner** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

TRANSPORTATION INFORMATION

DOT Road Shipment Information

Not subject to DOT.

Air Shipment (IATA)

Not subject to IATA regulations.

Ocean Shipment (IMDG)

Not subject to IMDG code.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



Dynatex
350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418
Outside U.S.
TEL +1(270) 769-5557
FAX +1(270) 769-6418

Email: sales@dynatexinc.com
Website: www.dynatexinc.com

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066