

Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 1 - Chemical Product and Company Identification

- 1.1 Product Name: M1
- 1.2 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744
- 1.3 Recommended Use: Racing Fuel
- 1.4 RESTRICTIONS on USETHIS FUEL IS FOR RACING VEHICLE USE ONLY! NOT LEGAL FOR STREET DRIVEN MOTOR VEHICLE
- 1.5 Emergency Telephone: CHEMTREC 800-424-9300 International Emergency Telephone Number: +1-703-527-3887
- 1.6 See Section 16.3 for CHEMTRC in Country Emergency Numbers
- **1.7 Supplier:** Segedin Truck & Auto Parts Limited (STA Parts), 53 Andrew Baxter Drive, Airport Oaks, Auckland Airport 2150, New Zealand, Phone Number: +64 9 256 1120

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Highly Flammable liquid/vapor
Specific Target Organ Toxicity single exposure
Carcinogenicity
Eye Irritation
Skin Irritation
Acute Toxicity (Oral)
Acute Toxicity (Inhalation)

2.2 Signal Word: Danger

Acute Toxicity (Dermal)

Hazard Categories

Category 2

Category 1

Category 1A

Category 2A

Category 2

Category 3

Category 4

Category 3

Page 1 of 10

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of



2.3 Pictograms:

Flame

Health hazard Toxic

2.4 Hazard Statements

PHYSICAL HAZARDS: H225: Highly flammable liquid and vapor

HEALTH HAZARDS: H301 + H311: Toxic if swallowed or in contact with

skin

H315: Causes skin irritation

H319: Causes serious eye irritation

H332: Harmful if inhaled H350: May cause cancer

H370: Causes damage to organs

PRECAUTIONARY STATEMENTS: P102: Keep out of reach of children

P202: Do not handle until all safety precautions have

been read and understood

P210: Keep away from sparks and open flames- No

smoking

P260: Do not breathe vapors

P280: Wear protective gloves, clothing and eye

protection

RESPONSE STATEMENTS:

P301 +310+ P331: IF SWALLOWED: <u>USA</u> Immediately call the National POISON CENTER at 800-222-1222. OUTSIDE USA Immediately call poison center or

doctor.DO NOT induce vomiting

P303+P361+353: IF ON SKIN Take off immediately all

contaminated clothing. Rinse skin with water

P304+340: IF INHALED, Remove to fresh air and keep

comfortable for breathing

P305+P351: IF IN EYES rinse cautiously with water

for at least 15 minutes

P306+P361: IF ON CLOTHING, Take off contaminated

clothing

P370: In case of fire use foam, carbon dioxide, dry

chemical to extinguish fire

P376: Stop leaks if safe to do so. See section 6 for

proper clean up

STORAGE STATEMENTS: P403: Keep Cool Store in a well-ventilated place

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of

the Work Health and Safety Act

DISPOSAL STATEMENTS:

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Other Identifiers
67-56-1	200-659-6	Methanol	100%	Methyl Alcohol

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

- 4.5 After first aid, get appropriate paramedic, or community medical support.
- **4.6 Note to Physicians:** The severity of outcome following ingestion may be more related to the time between ingestion and treatment, rather than the amount ingested. Therefore, there is a need for rapid treatment of any ingestion exposure.

Section 5 - Fire-Fighting Measures

- **5.1 General Fire Hazards** Use water to cool containers exposed to fire
- **5.2 Hazardous Combustion Products** Avoid fumes of burning product.
- **5.3 Extinguishing Media** Carbon dioxide, dry chemical, and foam.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

5.4 Fire Fighting Equipment/Instructions Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

- **6.1Spill /Leak Procedures:** Ventilate area highly flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.
- **6.2 Spills:** Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

- **7.1 Handling Precautions:** Keep away from ignition sources such as heat, sparks and open flames NO SMOKING Take precautionary measures against static discharge. Non sparking tools should be used. Wear protective gloves, clothing and eye protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death.
- **7.2 Storage Requirements:** Store in original manufacture container tightly closed container in a cool, dry and well-ventilated area.
- 7.3 Chemical Incompatibilities: Strong oxidizing agents and strong reducing agents.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL	
Methanol Methanol	200ppm TWA	*250 ppm TWA	

STEL = Short-term Exposure Limit.

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded."

*Listed on the OSHA Z1 Table

- **8.2 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.
- **8.3 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

8.4 Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe

Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

Full contact: Butyl-rubber Splash contact: Nitrile rubber

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing and the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

8.5 Protective Clothing Pictograms











9.1

Physical State: Liquid Appearance: Clear Odor: Pungent

Vapor Pressure: 141mmHg@21°C Vapor Density (Air=1): 1.1 Specific Gravity (H₂O=1,): .75

pH: N/A

Water Solubility: Completely miscible Flash Point 49.5 °F, 9.7 °C - closed cup

Boiling Point: 149 °F, 65 °C

Freezing/Melting Point: -144 °F, -98 °C

Viscosity: Not Available

Auto ignition Temperature: 851.0 °F, 455.0 °C at

1,013 hPa (760 mmHg)

LEL: 6% UEL: 36%

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks open flames and other ignition sources.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 11- Toxicological Information

11.1

Product Name	Results	Species	Dose	Exposure
Methanol	Oral LDLO	Human	143mg/kg	None Listed
Methanol	Oral LD50	Rat	2131 mg/kg	None Listed

- **11.1.1** OECD Guideline 401 Tests results found in the European Chemical Agency Data Base shows that components of this product to be Acute Oral Toxicity.
- **11.11.2** OECD Guideline 403 Tests results found in the European Chemical Agency Data Base shows that components of this product to be Harmful Oral Inhalation.
- **11.11.3** OECD Guideline 402 Tests results found in the European Chemical Agency Data Base shows that components of this product to Acute Dermal Toxicity
- 11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin and/or Eye Contact
- 11.3 Aspiration Hazard: None
- 11.4 Skin Corrosion/Irritation: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
- 11.5 Serious Eye Damage/Irritation: Causes eye irritation.
- **11.6 Specific Target Organ Toxic**ity (Single Exposure): May cause damage to the following organs: Eyes, Kidney, Liver, Heart, Central nervous system.
- 11.7 Specific Target Organ Toxicity (Repeated Exposure): None Found
- **11.8 Signs and Symptoms:** Effects of overexposure can include Methyl alcohol may be fatal or cause blindness if swallowed. Effects due to ingestion may include: Headache, Dizziness, Drowsiness, metabolic acidosis, Coma, Seizures. Symptoms may be delayed.
- **11.9 Carcinogenicity:** OECD Guideline 453 Tests results found in the European Chemical Agency Data Base shows that components in this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA	
Methanol	Not listed	Confirmed Human	Not listed	Not listed	
		Carcinogen		3.00	

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure		
Methanol	LC50 29.4 mg/L	Fish	96 hours		
Methanol	LC50 22,200 mg/L	Daphnia	48 hours		

- **12.2 Toxicity:** This chemical is not regarded as toxic to aquatic organisms. However **DO NOT** discharge into a sewer or waterway.
- **12.3 Mobility:** Floats on water, absorbs to soil and has low mobility.
- **12.4** Persistence/degradability: This product contains no components that may persist in the environment.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

12.5 PBT and vPvB assessment: This substance is not considered to be persistent, bioaccumulating nor toxic (PBT). This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 US Transport Information



ID No.: UN 1230 Shipping Name: Methanol Hazard Class: 3, (6.1) Packing Group: Il Label: Flammable, Toxic Placard: Flammable, Toxic

14.2 TDG Canadian Transport Information



ID No.: ID No.: UN 1230 Shipping Name: Methanol Hazard Class: 3, (6.1) Packing Group: II Label: Flammable, Toxic Placard: Flammable, Toxic



Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

14.3 IMDG Transport Information



ID No.: UN 1230

Shipping Name: METHANOL Hazard Class: 3, (6.1)
Packing Group: II

Flash Point: 9.7 °C - closed cup

EmS Number: F-E, S-E Label: Flammable, Toxic Placard: Flammable, Toxic

14.3 ADR/RID Transport Information



ID No.: UN 1230

Shipping Name: Methanol Hazard Class: 3, (6.1) Flash Point: 9.7 °C - closed cup

Packing Group: II

Label: Flammable, Toxic Placard: Flammable, Toxic

Australian Dangerous Goods Transport Information



ID No.: UN 1230

Shipping Name: Methanol **Hazard Class:** 3, (6.1)

Flash Point: 9.7 °C - closed cup

Packing Group: II
Label: Flammable, Toxic
Placard: Flammable, Toxic
Hazman Code: 2WE HIN 336

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 15 - Regulatory Information

15.1 US Regulations

TSCA: Methanol

CERCLA Hazardous Substances and corresponding RQs: Methanol 5000 pounds

SARA Community Right-to-Know Program: Methanol

Clean Water Act: None

Clean Air Act: Methanol

OSHA: All ingredients are regulated by 1910.1200

State Regulations

California prop. 65: Methanol Developmental

Chemicals on the following State Right to Know Lists:

Massachusetts: Methanol

New Jersey: Methanol

Pennsylvania: Methanol

15.2 Canadian Regulation:

The following substances are specified on the public Portion of the Domestic Substances List (DSL):

Methanol

15.3 Europe Regulations

All substances contained in this product are listed on the EU directives or are not required to be listed.

15.4 International Regulations:

Australian Inventory of Chemical Substance: All components of this product are on the Inventory or are exempt from Inventory requirements.

National Existing Chemical Inventory in Taiwan: All components of this product) are on Inventory or are exempt from Inventory requirements.

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements.

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

16.2 References: CHEMpendium data base of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller on Line, European Chemical Agency Data Base and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC In country emergency dial numbers:

Australia (Sydney) + (61)-290372994 China 4001-204937 must be call within China Germany 0800-181-7059 must be call within Germany Germany (Frankfurt) + (49)-6964350840 Russia 8-800-100-6346 Must be call within Russia

